

HD-NDI3-120

The best livestreaming POV high-frame capture camera to date!

The HD-NDI3-120 transcends the boundaries of what was possible into a new realm of infinite possibilities. This camera stands as one of the pioneers that boasts capturing up to 120fps at a stunning 1080p resolution through both NDI HX and HDMI. With this impressive frame rate, you have the freedom to slow down live footage, capturing each moment frame by frame, resulting in awe-inspiring slow-motion sequences that will elevate your live-stream. Furthermore, this camera introduces a new style as our first NDI HX3 POV camera in the market, delivering our trusted AIDA form factor and an unparalleled user experience that truly sets the HD-NDI3-120 apart.

So unleash the limitless potential of livestreaming with the HD-NDI3-120, either through the power of high-frame capture, or HX3.



KEY FEATURES:



APPLICATIONS:



FAST ACTION SPORTS



MOTION CAPTURE



POV SHOTS



INDOOR EVENTS



MUSIC VENUES

*NDI® is a registered trademark of Newtek, Inc.

MAIN FEATURES


- Full-HD 1/3" Progressive Scan CMOS sensor capable of capturing 1080p 120fps over NDI|HX and HDMI
- HX 3 Capable camera outputting up to 1080p 60fps at 60mb, 4 times the amount of HX!
- Accessible Web UI to stream directly to social media platforms and control image parameters over IP.
- Versatile design with top & bottom tripod mounts for unqiues shot creation.
- Camera is PoE+ Capable. Just plug in one wire for power, control and video!
- Small form-factor and rugged designed makes all video streaming applications possible
- Small tally light on front of camera to ensure talent of when camera is live or about to be.

SPECIFICATIONS


VIDEO		LENS	
Image Sensor	1/3" Progressive CMOS	Lens	5MP 4mm CS Mount HD Lens
Effective Pixels	Horizontal: 1920, Vertical: 1080		FOV: 86°
Pixel Size	2.13 μm (H) x 2.13 μm (V)	AUDIO	
Resolution	1080p, 1080i, 720p	Audio Embed	Embed over HDMI and IP streaming
Resolution Rate	NDI HX/HDMI ONLY: 1080 120p, 100p HX 3 and Others: 1080 60p/59.94/50p/30p/ 29.97p/25p/24p 1080 60i/59.94i/50i 720 60p/59.94p/50p	Input	3.5mm Line Input
Output	HDMI / IP (NDI HX3/SRT/RTMP/RTSP)	STANDARD	
Color Space	4:2:2 (YCbCr) 10bit	IP Protocol	UDP IP, RTSP RTMP, SRT, NDI HX
Min Illumination	0.2Lux (day), 0.1Lux (Night)	PHYSICAL	
White Balance	Auto & Manual (9000 - 11,000 K)	Camera Control	Protocol: VISCA Over IP
		Operation Temp	32°F - 104°F
		Dimension	85mm x 49mm x 49mm 3.35" x 1.93" x 1.93"
		Weight	350g / 1 lb
		Power	12VDC (+9 - +15VDC), PoE+ (standard IEEE802.3at)

*Specification are subject to change without notice.

PACKAGE CONTENTS



DC 12v Power Supply & Sockets Adapter




4mm 5MP Lens (Pre-Installed)



USB Cable



C-Mount Cap Adapter



Sensor Cap

*NDI® is a registered trademark of Newtek, Inc.

At AIDA Imaging, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters. From concept to reality, AIDA Imaging meticulously creates products that are applicable to various solutions, effective for the global user.