

DIREKT LINK 300 & 400



Send high quality compressed video over Internet and other IP nets

STANDARD FUNCTIONS

- Multiple outputs
- Constant bitrate in pre-configured encoding modes
- Adaptive encoding parameters for automatic handling of the capacity of Internet connection
- Network bonding uses several Internet connections for higher capacity and redundancy
- Scales input signal to encoding resolution of choice
- Easy to configure via display and keypad
- Can be controlled via web interface over network
- Create profiles for multiple destinations
- Peak Programme Meter for calibration of sound level
- Record to files by connecting a USB storage
- Download recorded files from web interface
- ISS – Intinors system for statistics, supervision and troubleshooting
- Backup and upgrade via web interface or ISS
- Send to a number of different types of receivers
- Create your own encoding settings
- Test picture can be encoded and customized
- Management via IP2 (secondary network interface)
- IPMI (only on rack models)

Functions for web TV

- Send video using RTMP to Adobe Streaming Server and Wowza Media Server
- Supports multiple resolutions and frame rates
- Record files in .flv-format

Functions for broadcast on 400 series

- Send streams using UDP for shortest possible delay
- Interlaced video and anamorphic resolutions
- FEC - forward error correction with low delay

DIFFERENT MODELS

Direkt link	300-series (webTV)		400-series (Broadcast)		
	Mobile*	Rack	Mobile*	Rack	Rack+
Format	Mobile*	Rack	Mobile*	Rack	Rack+
Inputs	1xSDI 1xHDMI	2xSDI	1xSDI 1xHDMI	2xSDI	2xSDI
Audio	2	8	2	16	16
Built in mixer	Yes	-	Yes	-	-
Webb HD/ SD out	Yes	Yes	Yes	Yes	Yes
Broadcast HD/SD out	-	-	Yes	Yes	Yes
Internal storage	-	Option	-	Option	Option
Redundant power supply	-	Option	-	Option	Yes
Network bonding	Yes	Yes	Yes	Yes	Yes
FEC	-	-	Yes	Yes	Yes

DIFFERENT FORMATS

Rack

Direkt link are usually delivered in a format which can be installed in a 19" rack with all connections on the rear side. Power supply is built in and 100 – 240V AC is fed using an ordinary power cord.

Mobile*

For a Direkt link which is often moved around, the mobile format is recommended. Power supply is external, which makes it easy to run Direkt link from battery when needed (9–24V DC). Built-in 3G/4G modem



* Not available in all regions



Formvägen 16, 906 21,
Umeå, Sweden



+46 (0) 90-349 39 00



info@intinor.se



www.intinor.se

OPTIONS

Direkt link is primarily customized using options. Other customer tailored solutions are made on order.

4-wire talkback

By using 4-wire talkback, Direkt link can connect to other Direkt units for audio communication with short delay. The option gives two full duplex mono channel, for example control room and studio return.

Multiple 4G*

All Direkt Links have network bonding as standard, but can be be equipped with the ability to use multiple 4G modem.

Battery cable

Direkt link mobile can be equipped with battery cable to run on camera battery

Case

All Direkt links can be delivered in custom cases.

Extra encoder

Direkt link can encode the input signal to one or multiple other encoding modes. For example if one want to record in higher quality or send in multiple qualities.

Internal hard disk

Direkt link which is often used for recording video can be equipped with internal hard disk or a RAID system with multiple disks.

Encryption

The video stream between Direkt link 400 series and Intinors Direkt receiver can be encrypted and authenticated in a very secure way if needed.

Automatic file sync using FTP

When a new file is ready on the Direkt link or router and live streaming has stopped, it automatically uploads the file.

MPEG2

MPEG2 is still often used for distribution to cable TV. It can also be wise to record in MPEG2 format since it's usually faster to import and work with in different video editing programs.

TECHNICAL SPECIFICATIONS

Digital out SDI embedded	SMPTE 259M, SMPTE 272M PAL, NTSC 0-16 audio channels
Digital in HDSDI embedded	SMPTE 292M, SMPTE 299M 720p/50, 720p/59.94, 720p/60, 1080p/23.98, 1080p/24, 1080p/50, 1080p/60, 1080i/25, 1080i/29.97, 1080i/30 0-16 audio channels
Digital in HDMI	Only on Direkt link mobile
Digital video ut H.264	H.264/MPEG4 AVC video (ISO/IEC 14496-10) BP@L3.0 - HiP@L5.1 (4:2:0)
Digital video ut MPEG2 (option)	MPEG2 video CBR (ISO/IEC 13818-2) MP@ML, MP@HL, HP@ML, HP@HL (4:2:0) 422@ML, 422@HL (4:2:2)
Digital audio out	MPEG1 audio layer 2 (ISO/IEC 11172-3) AAC (ISO/IEC 14496-3:2005) MAIN
Transport out TCP	MPEG2-TS over IP (ISO/IEC 13818-1) RTMP adaptive bitrate
Transport out UDP (only on broadcast models)	MPEG2-TS overIP (ISO/IEC 13818-1) UDP and RTP (RFC 3550, RFC 2250)
Error corrections UDP (only on broadcast models)	FEC: Pro-MPEG COP #3, SMPTE ST 2022-1:2007
Interface out	2 Ethernet 10/100/1000, RJ45 Extra RJ45 via external USB-LAN
4G/LTE	Built-in on mobile Direkt links External USB modem on rack models
Hard disk for archiving	Extern USB2.0 / USB3.0
Size rack (without removable rack brackets)	425 x 380 x 45 (w x d x h) Fits in 19" rack(1U)
Size mobile	190 x 150 x 75 (w x d x h)
Weight approximately	5200g (rack) 1500g (mobile)
Power consumption	Max 100W (rack) Max 60W (mobile)

* Not available in all regions