


■ 4K CMOS 1/2.5 inch Image Sensor

The KY-PZ400N is equipped with a 4K 1/2.5" CMOS image sensor with 8.51M effective pixels. The KY-PZ200N/PZ200 is equipped with an HD 1/2.8" CMOS image sensor with 2.07M effective pixels.

■ 12x Zoom (KY-PZ400N), 20x Zoom (KY-PZ200N/200)



■ Support H&V Flip, Image Freeze, 255 Preset Positions, 0.1° Preset Accuracy



HDMI Output 3G-SDI	Type A BNC type, 800mVp-p, 75Ω, Along to SMPTE 424M standard	
Network Interface	RJ45 : 10BASE-T/100BASE-TX/1000BASE-T	
Audio Interface	Line In/Out: \oplus 3.5mm audio interface	
USB	USB2.0, A type (for maintenance) USB3.0, B type (KY-PZ200N/KY-PZ200 only)	
Communication Interface	RS232 In/Out : 8pin Min DIN, Max Distance : 30m, Standard Protocol RS485 : 2pin Phoenix Port, Max Distance : 1200m, Standard Protocol	



KY-PZ200N/PZ200

60.7° ~ 3.36°

34.1° ~ 1.89°

±170°

-30° ~ +90°

■ Network

	KY-PZ400N	KY-PZ200N	KY-PZ200
Video Compression	H.264/H.265/Motion JPEG		
Video Stream	Main Stream, Sub Stream		
Protocols	Control: NDI HX, Standard Streaming: RTSP/RTP, RTMP/RTMPS, SRT, NDI HX		Control : Standard Streaming : RTSP/RTP, RTMP/RTMPS, SRT
SRT Mode	Listener, Caller, Rendezvous (Future update)		
UVC	Not Supported UVC 1.1-1.5		




NDI is a high quality, low latency, IP video transmission standard pioneered by NewTek.



SRT advanced streaming uses automatic repeat reuest (ARQ) and forward error correction (FEC) to prevent packet loss typical for internet connections. SRT also offers stream encryption for content protection.

■ Multi Camera Synchronization with VITC (Vertical Interval Time Code) NTP (Network Time Protocol)

Multi-camera synchronization for live event productions is simply achieved with VITC with NTP. This feature is ideal for the mixing and streaming of concerts, shows and sporting events where image synchronization is critical.



■ Supported Remote Controls (Remote Production over the Internet)

Remote Camera Controller RM-LP100

DISTRIBUTED BY





LIVE STREAMING
PRODUCTION SUITE
KM-IP6000/4000
Series
*Future Update










■ General Specification


	Tally: 1x Red/Green (KY-PZ400 only)		
LED	Power : 1x Blue		
	Standby : 1x Yellow-green		
Input Voltage AC Adapter: DC 12V PoE: DC 37-57V			
PoE Supply	802.3af Standard		
Operating Temperature	0°C ~ 40°C		
Storage Temperature	-20°C ~ 50°C		
Size	D168.4mm x W141.5mm x H164.5mm (D6.6 inch x W5.6 inch x H6.5 inch)		
Net Weight	KY-PZ400 : 1.7kg (3.7 lbs) KY-PZ200N/200 : 1.6kg (3.5 lbs)		
Language	English, Chinese, Japanese, German, Spanish, Russian, French, Italian		
Accessory AC Power Adapter, Power cable, RS232C IR Remote Control, Ceiling Bracket, Logo S			

NDI is a trademark or registered trademark of Vizrt Group in the United States and other countries. Product and company names mentioned here are trademarks or registered trademarks of their respective owners.









Drawing: KY-PZ400N

Simulated pictures. Values for weight and dimensions are approximate. E.&O.E. Design and specifications subject to change without notice. Copyright © 2021, JVCKENWOOD Corporation. All Rights Reserved.

JVC Professional Video Website







eu.jvc.com/pro