

Spark™ Plus IO 4K Technical Specifications

Video Input	1 x HDMI
Video Output	1 x HDMI
Audio Input	1 x HDMI embedded audio input 1 x 3.5 mm analog stereo line level
Audio Output	1 x HDMI embedded audio output 1 x 3.5 mm analog stereo line level
Encoding Decoding	NDI®
Networking	1 Gigabit Ethernet
Interface	Web-based user interface for configuration and monitoring
Tally	Tally support via NDI®
Formats	2160p: 60, 59.94, 30, 29.97, 25 1080p: 60, 59.94, 50, 29.97, 25 720p: 60, 59.94, 50, 29.97 576p: 50 480p: 60, 59.94
Power	Power over Ethernet or external power adaptor
Physical	Portable enclosure with threaded screw camera mount <ul style="list-style-type: none"> • 3.94 x 3.15 x .94 in (100 x 80 x 24 mm) • .53 lbs (.24 kg)

Subject to change without notice.

Spark™ Plus IO SDI Technical Specifications

Video Input	1 x 3G-SDI
Video Output	1 x 3G-SDI
Audio Input	1 x SDI embedded audio input 1 x 3.5 mm analog stereo line level
Audio Output	1 x SDI embedded audio input 1 x 3.5 mm analog stereo line level
Encoding Decoding	NDI®
Networking	1 Gigabit Ethernet
Interface	Web-based user interface for configuration and monitoring
Tally	Tally support via NDI®
Formats	1080p: 60, 59.94, 50, 29.97, 25 720p: 60, 59.94, 50, 29.97, 25
Power	Power over Ethernet or external power adaptor
Physical	Portable enclosure with threaded screw camera mount <ul style="list-style-type: none"> • 3.94 x 3.15 x .94 in (100 x 80 x 24 mm) • .53 lbs (.24 kg)

Subject to change without notice.